



INSTALLATION DO'S AND DON'TS

When installing the Enviroshake product, there are specific areas of the installation procedures that ALL projects must have addressed properly to provide the longest lasting and best performing roofing system and provide the Property Owner with a warrantable project.

- DO** GAP every shake 3/8" including the starter row (not gapping will void the warranty)
- DO** nail or screw INSIDE the "O" nail markings (missing the attachment marker will void the warranty)
- DO** leave a minimum of 1 1/2" between keyways from the next lower course (too close of keyways, will void the warranty)
- DO** install Enviroshake directly on the roof surface over the underlayment (DO NOT install over existing roofing)
- DO** use 1 1/2 inch ring shank roofing nails (anything less than the 1 1/2" may void the warranty)
- DO** use the Peel-N-Stick underlayment provided by Enviroshake
- DO** factor 8-10% for waste

- DO NOT** use red chalk for chalk lines (red chalk will stain the product and this staining is not covered by the warranty)
- DO NOT** have any nail heads showing (visible nail heads may cause the system to have vulnerability of water infiltration)
- DO NOT** break each shake (unless you are staggering the course or using mixed colors)
- DO NOT** break slates
- DO NOT** interweave (when using a synthetic underlayment)
- DO NOT** install on roofs less than a 2/12 pitch
- DO NOT** use product from one project to another (doing so may create a color discrepancy due to production batches)

DO NOT FORGET TO GAP!

For more information, contact Enviroshake at
1-866-423-3302 or 1-519-380-9265